



Document Solutions

> PRINT > COPY > SCAN > FAX

ECOSYS M4125idn

MONOCHROME
MULTIFUNCTION PRODUCT
FOR A4/A3 FORMAT

NEW DESIGN
NEW DEFINITION



KYOCERA MyPanel



Mobile Print



Cloud Connect



- Breakthrough design for easy use, control and service.
- High image quality with 1,200 x 1,200 dpi print resolution.
- Fast first copy time (mono: 5.8 seconds).
- Excellent clarity color touch panel display.
- Fast scanning up to 50/50 ipm A4 Mono/Color.
- Convenient wireless LAN interface*.
- Support Air Print and Mopria certified.
- Long life drum and replacement parts provide efficiency and reliability.
- Compact design and low noise emission.

*Optional

ECOSYS®

			Main Specifications
Model			ECOSYS M4125idn
Main Function			Copy, Print, Scan, Fax (Optional)
Writing Method			Semiconductor Laser
CPU			ARM Cortex-A9 (Dual Core) 1.2GHz
Print Speed (A4) (Mono/Color)			25/ - ppm
Scanning Speed (A4) 300dpi	Simplex(Mono/Color)		50/50 ipm
	Duplex(Mono/Color)		16/16 ipm
Memory			Standard 1GB (Max. 3GB)
SSD Capacity			SSD 32GB (Optional) / SSD 128GB (Optional)
Warm Up Time			20 seconds or less
Paper Capacity	Standard		600 sheets [1 x 500 sheets (Cassette) + 100 sheets (MPT)]
	Maximum		1,600 sheets (Main Unit + 2 x 500 sheets PF-471 x1 + MPT)
Paper Size	Cassette		Min. A5R - Max. A3 (Ledger)
	MPT		Min. A6R - Max. A3 (Ledger)
Paper Weight	Cassette		60 - 163 g/m ²
	MPT		45 - 256 g/m ²
Duplex Printing			Paper size: A5R – A3; Paper weight: 60 - 163 g/m ²
Output Capacity			Max. 250 sheets + 50 sheets with standard Job Separator
Control Panel			4.3-inch Color Touch LCD Panel
Document Processor			Standard (Max. 50 sheets RADF Type)
Dimension (W x D x H) (Main Unit)			590mm x 590mm x 688mm (with DP)
Weight (Main Unit)			Approx. 72 kg
Power Consumption (Standard configuration)	Copy/Print Mode		390W
	Stand-by Mode		55W
	Energy Saver		0.5W
Noise (ISO7779/ ISO9296)	Copy/Print Mode		49dB(A)
	Stand-by Mode		34dB(A)
Copy Functions (Standard)			
Copy Size			Max. A3 (Ledger) – Min. A6R
Resolution			600 x 600 dpi
First Copy Time (Mono/Color)			5.8/ - seconds
Zoom Ratio	Manual		25% - 400% (1% per Step)
	Pre-defined		5RSE
Multiple Copy			1 – 999
Print Functions (Standard)			
Resolution			600 x 600 dpi; 1,200 x 1,200 dpi
PDL			PRESCRIBE, PCL6, KPDL3 (Postscript 3 compatible), XPS, PDF Direct Print Ver. 1.7
First Print Out Time (Mono/Color)			5.8/ - seconds
Network Printing			TCP/IP, NetBEUI, FTP, Port 9100, LPR, IPP, IPP over SSL, WSD Print, Apple Bonjour
Operating System Supported			Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows 10; Apple Macintosh OS X 10.5 or later; Linux
Interface			USB 2.0 High Speedx1; Ethernet 10BASE-T/100BASE-TX/1000BASE-T; USB Host Interface (USB Host)x2; NFC TAGx1; 802.11 b/g/n/Wireless LAN/WiFi Direct (Optional)
USB Memory Printing Format			TIFF, JPEG, PDF, XPS, Open XPS
Mobile Printing			AirPrint, Mopria, KYOCERA Mobile Print
Scan Functions (Standard)			
Color Selection			Auto Color (Color/Gray); Auto Color (Color/B&W); Full Color; Grayscale; Black & White
Resolution			600dpi, 400dpi, 300dpi, 200dpi, 200x400dpi, 200x100dpi
File Format			TIFF, JPEG, XPS, OpenXPS, PDF (High-compression PDF)
Image Type Mode			Text, Photo, Text + Photo, Light Text (Fine Line)
Transmission Type			Scan to SMB; Scan to E-mail (SMTP, SMTP over SSL); Scan to FTP or FTP over SSL; Scan to USB; TWAIN Scan; WSD Scan; WIA Scan
Address Storage			200 addresses (Common address list), 50 groups (Group address list)
Fax Functions (Optional)			
Original Size			Max. A3 (Ledger) - Min. A5 (Statement)
Coding Method			MMR, MR, MH, JBIG
Transmission Speed			33.6 kbps
Memory			12MB
Network FAX			Yes
Consumables & Options			
Toner Kit			TK-6110
Maintenance Kit			MK-6119; DP: MK-6110
Paper Feeder			PF-470: 500 sheets x1; PF-471: 500 sheets x2
Finisher (ECOSYS M8130cidn / ECOSYS M4132idn only)			DF-470: 500 sheets Hanger Type Finisher; AK-470: Attachment Kit for DF-470
Fax System			Fax System 13
Storage Device			HD-6: SSD 32GB; HD-7: SSD 128GB
Data Security			Data Security Kit(E)
Card Authentication			Card Authentication Kit(B)
Gigabit Ethernet Board			IB-50: For Additional Network
Wireless LAN Interface			IB-36 (802.11 b/g/n/Wireless LAN/WiFi Direct)



บริษัท เคียวเซรา ด็อกคิวเม้นท์ โซลูชั่นส์ (ประเทศไทย) จำกัด
 โทร. 0-2586-0333 โทรสาร 0-2586-0278
www.kyoceradocumentsolutions.co.th

*KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA Business Partner

